

# KH1000 Specification


## Professional Hermetic Sliding Door

### Standard size



#### Single open(to L or R)

1.0x2.2m  
1.5x2.2m



#### double open

1.5x2.2m

Opening width (W)	900-1500mm
Max weight/single	120kgs
Max speed	0.5-0.7m/s

Opening width (W)	900-2800mm
Max weight/single	80kgs
Max speed	0.5-0.7m/s

### Technical Data

- |                           |                          |                         |       |
|---------------------------|--------------------------|-------------------------|-------|
| ●Power supply             | 230V±10%,<br>50/60Hz,13A | ●UPS backup battery     | 30min |
| ●Power Consumption        | 100W                     | ●Max. relative humidity | 90%   |
| ●Max Drive power (static) | 150N                     | ●Protection level       | IP23  |

### Standard

- |                  |                   |
|------------------|-------------------|
| ●Drive unit      | ●Rail beam        |
| ●Control unit    | ●Viewing window   |
| ●Aluminium frame | ●Invisible handle |
| ●Foot switch     | ●Key switch       |

### Optional

- |                         |                        |                           |
|-------------------------|------------------------|---------------------------|
| ●PSA control panel      | ●Operator top cover    | ●Anty-squeeze safety beam |
| ●Electromechanical lock | ●Lead protecting       | ●Operator side covers     |
| ●Backup battery unit    | ●Hand induction switch |                           |

### Doorbody

Aluminium panel  
Stainless steel panel